



Linklite Temporary Lighting

Linklite is designed to be daisy chained to illuminate long distances. With Linklite LED it's possible to floodlight in excess of half a kilometre using less than 2KW of generated power.



Stackable components

The luminaire, telescopic mast and steel basket all detach and stack for easy transportation and convenient storage.

Save over 80% in running costs

Compared to a standard 4000W light tower, a string of Linklites will light the same distance for less than one fifth of the running cost.

Water, dust and shock resistant

IP44 rated for outdoors. IEC 60309 quick release plugs and connectors. Highly durable polycarbonate lens casing ideal for construction sites.



Linklite LED 240V

Rated voltage	V	240
Rated wattage	W	30
Rated temperature	°C	50
Rated current	A	0.28
Lamp CCT	K	6500
Total lamp lumens	L	4000
LED lifespan	Hrs	20,000 +
Luminaire LxWxH	mm	546 x 273 x 135
Luminaire weight	kg	3.3
Mast height	m	1.8 - 2.8
Mast weight	kg	1.95
Base LxW	mm	510 x 460
Base weight	kg	5.86
Ingress protection		IP44
Compliance		AS/NZS 60598.1:2013 & AS/NZS 60598.2.4:2005 +A1



***Please note:** Details, including technical specifications are correct at the time of printing, subject to change without notice. Every reasonable effort has been made to ensure the information in this brochure is accurate. Green Power Solutions accepts no liability or responsibility for any errors or omissions occurring in or from this brochure. Consult with your Green Power Solutions representative for further information.