



**ITALTOWER®**  
HEAVY DUTY LIGHTING TOWERS

**OKAPI PRO01**



Image for illustration purpose only.

Floodlight  
4x320W LED

Lumen  
166.200 lm

Light coverage  
5000 sq m

Italtower Srl

Via Meucci 5-11, 35028

Pieve di Sacco (PD) – Italy

P.Iva 04725890281

[www.italtower.com](http://www.italtower.com)

[info@italtower.com](mailto:info@italtower.com)





**Technical Specification**

Rated frequency	50 Hz
Rated Voltage	230 V
Rated Power	3.5 Kw
Operating temperature	-40/+50
Sound Level	61 dB
Control unit	DeepSea L401
Auxiliary power	2 kVA

**Engine**

Model	Kohler KDW702
Speed	1500 rpm
Coolant	Liquid
Cylinders	2
Emissions	Stage V

**Alternator**

Model	Linz Alumen
Rated outlet	3,5 kVA

**Energy consumption**

Fuel consumption	0,55 l/h
Tank	240 l
Fuel	Diesel
Running time	436 h

**Galvanized mast**

Height	8.5 m
Mast	Hydraulic
Rotation	355 °
Wind speed resistance	110 km/h

**Canopy & Trailer**

Trailer	Stationary
Tyres	/
Basement	Bunded base 110%
Stabilizers	4
Canopy	Powder coating paint

**Optional**

Optional included as standard	Dusk to dawn sensor with Autostart Grid/engine selector Battery isolator
-------------------------------	--

**Shipment**

Dimension	235x147x240 cm
Weight	850 kg
Truck	22 units
Container 40''	18 units

